



Update on Validation of AIRS Radiances, Retrievals, and OLR Products

Hank Revercomb, Dave Tobin, Fred Best, Bob Knuteson, Leslie Moy, Lori Borg, Joe Taylor, Steve Dutcher, and the whole Scanning HIS Team

University of Wisconsin-Madison pace Science and Engineering Center (SSEC)

AIRS Science Team Meeting 9-12 October 2007



Radiance Validation

- > JAIVEx: new data for IASI and AIRS
- > The NIST Connection: Recent results

Mission Metop Organization Instrument Ground segment

Applications | A S |

METOP

- · Eumetsat Polar System Elements
- 14 years of operation
- >95% reliability on 5 years

IASI on Metop
19 October 2006 launch

- full cross-track scan
- 2x2 12 km pixels sample 50x50 km



METOP 2 - 2010

METOP 3 - 2015











Cross-track scan pattern for 3 Sample Granules



Sample IASI spectra Level 1c (apodized to 0.5 cm⁻¹, Nyquist sampled) & PC noise filtered 180 [[] Wavenumber (cm⁻¹)

IASI T_b Spectrum:

Processed to represent S-HIS & NAST-I, AIRS & CrIS





Joint Airborne IASI Validation Experiment (JAIVEx)




- ◆ What: Metop and Aqua satellite under-flights for radiance and retrieval validation (IPO/UK/EUMETSAT supported)
- ◆ Who: NPOESS Airborne Sounder Testbed team (NAST-I/M & S-HIS on NASA WB57) & UK team (ARIES on Facility for Airborne Atmospheric Measurements BAe146-301)
- ◆ **When:** 14 April to 4 May 2007
- ◆ Where: Comparisons over the Gulf and Oklahoma ARM site reached from Houston airbase

Flight over ARM SGP, 19 April 07






All Bands




IASI, NAST-I, and SHIS Mean Spectra


(IASI L1C and NASTI spectra processed to match SHIS spectral resolution)

















IASI Shortwave Validation





Seven JAIVEx MetOp Cal/Val Flights



Four CART-site (2 day & 2 night); Three Gulf of Mexico (2 day & 1 night); Five joint MetOp & Aqua (3 day & 2 night)

Summary of Radiance Validation for climate

- The absolute calibration of IASI and AIRS
 Radiance are comparable and represent
 a huge improvement over past IR
 sounders for both weather and climate
 applications
- The value of aircraft observations for direct radiance validation has now been definitively proven
- Validation over their lifetime is still needed to assure the long-term stability




The NIST Connection for Scanning HIS and AIRS / IASI...


Why should you believe any of these measurements?



Scanning-HIS Radiometric Calibration 3-sigma Error Budget




21 November 2002 on ER2



16 November 2002 on Proteus

UW-SSEC AERI Blackbody Predicted Radiance Uncertainty


Uncertainty for $T_{BB} = 293K$, $T_{Refl} = 230K$




<u>3 σ Uncertainties</u>: $3\sigma T_{BB} = 0.05 \text{ K}$ $3\sigma T_{Refl} = 5 \text{ K}$ $3\sigma \epsilon_{BB} = 0.001$ Total (RSS)


UW S-HIS & AERI Blackbody Absolute Accuracy: The NIST Connection for true SI Traceability

Recent end-to-end radiance evaluations conducted under S-HIS flight-like conditions with NIST transfer sensor (TXR) such that S-HIS satellite validation & AERI observations are traceable to the NIST radiance scale






10 & 5 μm NIST TXR Channels



NIST TXR Validation of S-HIS Radiances

Preliminary Results: NIST TXR Channel 2 (10µm)

Differences wrt AERI Blackbody predicted radiance:




mean difference between TXR & S-HIS = 38 mK,
 well less than propagated 3-sigma uncertainties

NIST TXR Validation of S-HIS Radiances


Preliminary Results: NIST TXR Channel 1 (5µm)

Differences wrt AERI Blackbody predicted radiance:



- mean difference between AERI BB & S-HIS = 40 mK
- TXR Ch1 analysis requires refinement at this time

AERI Blackbody Reflectivity Test with NIST TXR Confirms Emissivity Estimates



7832 2932

January 2007

NIST Transfer Radiometer (TXR) used to detect reflection from heated tube (up to background +100 °C) surrounding direct FOV


Preliminary Analysis:
5 & 10 µm emissivity
within <0.0003
of expected value
(and closer to 1)




Analysis Summary

AERI Blackbody Reflectance

Updated August 07





Measurements confirm estimated emissivity well within uncertainty (3-sigma estimates)

*NIST analysis still being conducted





2. Retrieval Validation




- **◆** Temperature and water vapor profiles
- ◆ <u>Use three diverse ARM validation sites</u> mid-latitude/mid-continent, arctic, tropical western pacific




 Approach and v4 results in Tobin et al. (2006)

ARM represents the best available validation truth, and Dave Tobin in the best guy to interpret it

Atmospheric Radiation Measurement (ARM) Sites




AIRS Dedicated Radiosonde Launch Phases



5 "phases" conducted to date.
90 overpasses sampled from each site for phases 1 thru 4;
60 in Phase 5.

2007 phase finishing soon, ½ AIRS and ½ IASI


Temperature & Water Vapor Profile Distributions



Histogram of occurrence with higher being darker blue




TWP, v5-ARM and v4-ARM using v5 QC (v5 Pgood @surface)



Performance generally good, slight improvement in V5



SGP, v5-ARM and v4-ARM using v5 QC (v5 Pgood @surface)



Still not good P >750 mb, but Water Vapor significantly improved




NSA, v5-ARM and v4-ARM using v5 QC (v5 Pgood @surface)

Bias Dashed: RMS Solid P (mb) P (mb) 1000 L -1 1000 -20 -10 10 20 H₂O (%) -0.5 0.5 1.5 T(K) Surprisingly similar to SGP

Best Quality Retrievals: TWP, SGP, NSA

(Temperature at all levels, H2O, and Surface* best quality)




Note similarity of SGP & NSA




SGP: Land Surface Emissivity Problem

Based on UW AERI




v5 retrieved emissivity

AIRS retrievals
not a very
good match





SGP: Dependence of Retrieval Performance on Emissivity



The Good News: Significant improvement in lower trop RMS for both T and q when the retrieved $\epsilon_{12\mu m}$ is within range of SGP best estimates





- ◆ Alternative Radiative Transfer Model:

 RRTM applied to 16 Nov. 2002 AIRS retrievals for comparison to the TOVS model used for AIRS v5 L2 OLR
- **◆ CERES SSF OLR comparisons performed**(AIRS FOV defined as clear if all averaged CERES pixels had clear fractions greater than 99%)


We are working with Joel Susskind on this one

RRTM v3.01 from AER

(Tony Clough, et al.)

- Correlated k-distribution model
- ◆ Based on LBLRTM, line-by-line model developed under the ARM Program using AERI, microwave, & and a wide range of other data
- Computes LW and SW atmospheric flux and cooling rate profiles, clear and cloudy
- GCM version used in ECMWF and other Global Models
- Code and more information online at http://www.rtweb.aer.com

AERI Observations During SHEBA Improve Far-Infrared Radiative Transfer Models




Led to improved representation of far-IR H₂O continuum absorption in the

MT_CKD continuum model, included in LBLRTM and RRTM.


CERES OLR Maps

(16 Nov 2002)




AIRS-CERES Clear OLR Maps

(16 Nov 2002)




Latitude Dependence of Clear Sky AIRS OLR and CERES OLR




AIRS OLR consistently larger than CERES (order 4%)


Latitude Dependence of Clear Sky RRTM(AIRS) and CERES OLR



Good agreement--hard to tell them apart here


Latitude Dependence of AIRS OLR – CERES and RRTM(AIRS) - CERES







	Day (npts = $24,365$)		Night (npts = 23,286)	
	Mean	Stdev	Mean	Stdev
AIRS-CERES	9.4	5.5	8.7	8.8
RRTM-CERES	-1.8	3.3	-0.39	4.8


Upper Level Water Vapor Dependence of AIRS OLR – CERES and RRTM(AIRS) - CERES





Surface Temperature Dependence of AIRS OLR – CERES and RRTM(AIRS) - CERES





Conclusions

- ◆ Radiance Validation from aircraft platforms is excellent—needs to be continued until there is a well established alternative—e.g.CLARREO!!
- ◆ ARM site crucial as the most accurate atmospheric characterization for T/Q Retrieval Validation—future needs to be planned collaboratively with IPO
- ◆ AER's RRTM compares substantially better to CERES SSF than the current AIRS OLR*. The clear sky RRTM-CERES bias is about -1 W/m² (versus +9 W/m²), and has no latitudinal dependence. In fact, it is possible that the RRTM(AIRS) is more accurate than CERES itself.

^{*}Note the NASA AIRS L2 OLR model (Susskind) was developed ~1975 when there were still many outstanding spectroscopy issues

Backup Slides: Scanning HIS

UW Scanning HIS: 1998-Present

(HIS: High-resolution Interferometer Sounder, 1985-1998)

Characteristics

Spectral Coverage: 3-17 microns


Spectral Resolution: 0.5 cm⁻¹

Resolving power: 1000-6000


Footprint Diam: 2 km @ 20 km

Cross-Track Scan: Programmable

including uplooking zenith view



Relative Humidity Retrieval compared to lidar cloud boundaries




Applications:

- > Radiances for Validation & Radiative Transfer
- > Temp & Water Vapor Retrievals
- > Cloud Radiative Prop.
- > Surface Emissivity & T
- > Trace Gas Retrievals



UW Scanning HIS







S-HIS Aircraft Platforms



S-HIS Flight Experience



Sample Scanning HIS up and down views (from arctic MPACE, 10/17/04)



Atmospheric Spectral Calibration: S-HIS

